

## LAWN AND LEAF COLLECTION PRODUCTS

### Residential

#### TRACTOR VACUUM



#### Flex-Tube® PV (Medium Weight)

Coextruded Clear PVC hose with rigid black PVC helix

- Economical
- Ultra smooth interior, crush resistant
- OEM lengths and colors available
- Wall thickness .035"



SIZE 4", 5", 6", 7", 8", 10"

LENGTH 12', 25'

TEMP RANGE 20° to 160°

#### Flex-Tube® PU (Medium Weight)

Coextruded clear thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great abrasion resistance
- Ultra smooth interior, crush resistant
- Puncture and tear resistant
- OEM lengths and colors available
- Wall thickness .035"



SIZE 4", 5", 6", 7", 8", 10"

LENGTH 12', 25'

TEMP RANGE -65° to 200°

#### Flex-Tube® Bridge Clamps



Specially designed stainless steel band and welded stainless steel bridge with carbon steel screw

- Fits over helix creating a leak proof seal
- Available in sizes 4" to 10"

### Commercial/Landscaping

#### TRUCK LOADERS



#### Flexadux® LCDC (Medium Weight)

High performance polypropylene blend hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Economical
- Light weight, drag resistant
- Long flex life with good abrasion and tear resistance
- Wall thickness .032"



SIZE 8", 10", 12"


LENGTH 10', 25'

TEMP RANGE -30° to 200°

#### Flexadux® HT-W (Heavy Weight)

Thermoplastic rubber hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Great moisture and UV resistance
- External wearstrip offers additional drag resistance
- Puncture and tear resistant
- Wall thickness .045"



SIZE 8", 10", 12"

LENGTH 10', 25'

TEMP RANGE -40° to 275°

### Municipal Loaders

#### HEAVY-DUTY COMMERCIAL



#### Flx-Thane® HD (Heavy Weight)

Polyurethane hose reinforced with a coated spring steel wire helix

- Superior abrasion resistance & tear strength
- Ideal for leaf and debris collection
- Great moisture and UV resistance
- Excellent flexibility
- Also available in translucent blue
- Wall thickness .045"



SIZE 12", 14", 16", 18"


LENGTH 10', 25'

TEMP RANGE -65° to 225°

#### Flx-Thane® VHD (Very Heavy Weight)

Polyurethane hose reinforced with a coated spring steel wire helix

- Great abrasion resistance & higher tear strength
- Severe service & debris collection
- Great moisture and UV resistance
- Wall thickness .060"



SIZE 12", 14", 16", 18"

LENGTH 10', 25'

TEMP RANGE -65° to 225°

All 10' and 12' lengths are UPSable!

1510 Armstrong Road, Warsaw, IN 46581-4275

Toll Free: 800-343-0428 • Tel: 574-267-7909

Toll Free Fax: 800-382-8464 • Fax: 574-269-7491 • Email: sales@flexaust.com

www.flexaust.com



A SCHAUMBURG HOSE TECHNOLOGY COMPANY